






MULTIFIRE MODEL A

Multifire Model A is Model S with a long rod, it's spray can be regulated with one hand gesture for fog, direct jet or it can be closed entirely.

Model A is most commonly used as a washing nozzle in a hard to reach places. For example in ship yards, vessels and industrial use.



| Length | 2150 mm |
|------------------|---------------------|
| Weight | 3,0 kg |
| Nominal pressure | 10 bar, 230 psi |
| Material | Chrome plated brass |
| Inlet | BSP 1" or 2" male |

| RECOMMENDED HOSE DIAMETERS | | | | | | |
|----------------------------|---------------|---------------|---------------|--|--|--|
| 10A → Ø 25 mm | 12A → Ø 38 mm | 16A → Ø 52 mm | 19A > Ø 52 mm | | | |

6 BAR STRAIGHT STREAM 6 BAR 60° CONE FOG

| TYPE/SIZE | CODE NO | RANGE | FLOW RATE | RANGE | FLOW RATE |
|-----------|---------|-------|-----------|-------|-----------|
| 10 A | 1310A-0 | 28 m | 130 l/min | 12 m | 175 l/min |
| 12 A | 1312A-0 | 30 m | 155 l/min | 19 m | 215 l/min |
| 16 A | 1316A-0 | 29 m | 175 l/min | 12 m | 245 l/min |
| 19 A | 1319A-0 | 27 m | 210 l/min | 15 m | 275 l/min |